



5008

Réf.: 9627-PL

=1,00 h







NOTICE DE POSE A USAGE PROFESSIONNEL
 FITTING INSTRUCTIONS FOR PROFESSIONAL FITTERS, INSTRUCCIONES DE MONTAJE PARA USO PROFESIONAL,
 MANUAL DE MONTAGEM PARA UTILIZAÇÃO PROFISSIONAL, MONTAGEANLEITUNG FÜR PROFESSIONNELLEN EINSATZ,
 ISTRUZIONI DI POSA AD USO PROFESSIONALE, MONTAGEHANDLEIDING VOOR PROFESSIONEEL GEBRUIK

Type: 5001		
D 9,70 kN	94/20/EC e11 00-7303	

0 Km	1000 Km

	M6	1,1 daNm
	M10	4,2 daNm
	M12	6,5/7,5 daNm
	M12 (10.9)	9,5 daNm
	M10 (10.9)	6,2 daNm

A		x4 HM10	H		x2 HM6x20	
B		x4 M10	I		x2 HM6	
C		x4 HM10x45 (10.9)	J		x1 (1mm)	
D		x2 M12	K		x2 (2mm)	
E		x4 HM12x40 (10.9)	L		x2	
F		x4 HM12 (10)				
G		x2 HM12x60 (10.9)				





VCA Headquarters
 1 The Eastgate Office Centre
 Eastgate Road
 Bristol, BS5 6XX
 United Kingdom

Switchboard: +44 (0) 117 951 5151
 Main Fax: +44 (0) 117 952 4103
 Email: enquiries@vca.gov.uk
 Web: www.vca.gov.uk

APPROVAL NUMBER: e11*94/20*7303*00







INFORMATION PACKAGE CONTENTS

INDEX

REVISION NUMBER: Not applicable






Total number of sheets: 20 (Twenty)
 Number of separate drawings: 0 (Nil)
 Number of separate photographs: 0 (Nil)

Reasons for Revision: Not applicable



Revision date
 &
 Office stamp





APPENDIX I







to EEC Type Approval Certificate No: e11*94/20*7303*00






concerning the component type-approval of mechanical coupling devices
with regard to Directive 94/20/EC

1. ADDITIONAL INFORMATION
 - 1.1 Class of type of coupling: A50-X
 - 1.2 Categories or types of vehicles for which the device is designed or restricted: M, N
 - 1.3 Maximum D-value: 9.7 kN
 - 1.4 Maximum vertical load S at the coupling point: 100 kg
 - 1.5 Maximum load U at the fifth wheel coupling point: Not applicable
 - 1.6 Maximum V-value: Not applicable
 - 1.7 Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles: See manufacturers fitting instructions
 - 1.8 Information on the fitting of special towing brackets or mounting plates: Not applicable
5. Remarks⁽¹⁾: None

⁽¹⁾ Including information as to whether fifth wheel couplings are unsuitable for positive steering.

- (1) The EEC type approval number appearing on this document shall consist of all sections outlined in Annex VII to Directive 70/156/EEC as last amended by Directive 92/53/EEC. The component itself shall be marked as prescribed in the relevant separate Directive.
- (2) If the means of identification of type contains characters not relevant to describe the component types covered by this type approval certificate such characters shall be represented in the documentation by the symbol '?' (e.g. ABC??123??).





0.8 Name(s) and address(es) of assembly plants:

Thule Towing Systems B.V.
 Industrieweg 5
 7951 CX, Staphorst
 Netherlands


Thule Towing Systems B.V.
 Stephensonstraat 6
 7903 AV Hoogeveen
 Netherlands

Thule Towing Systems SARL
 ZAC des Naux
 51450 Bétheny
 France

Thule Towing Systems A/S
 Glasmagervej 21, Fensmark
 4684 Holmegaard
 Denmark

Thule Towing Systems AB
 Industrigatan 8
 46228 Vänersborg
 Sweden

SECTION II

1. Additional information (where applicable): See Appendix I
2. Technical service responsible for carrying out the tests: TÜV SÜD Automotive GmbH
3. Date of test report: 20 January 2009
4. Number of test report: 09-00020-CX-GBM
5. Remarks (if any): See Appendix I
6. Place: BRISTOL
7. Date: 04 FEBRUARY 2009
8. Signature:  A. W. STENNING
 Head of Technical and Quality Group
9. The index to the information package lodged with the competent authority that has granted type approval, which may be obtained on request, is attached.



VCA Headquarters
1 The Eastgate Office Centre
Eastgate Road
Bristol, BS5 6XX
United Kingdom

Switchboard: +44 (0) 117 951 5151
Direct line: +44 (0) 117 952
Main Fax: +44 (0) 117 952 4103
Email: enquiries@vca.gov.uk
Web: www.vca.gov.uk

THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY

COMMUNICATION CONCERNING THE GRANTING OF EEC TYPE APPROVAL AS A
COMPONENT OF MECHANICAL COUPLING DEVICES FOR MOTOR VEHICLES AND THEIR
TRAILERS PURSUANT TO DIRECTIVE 94/20/EC OF 30 MAY 1994 (STU)

Type Approval No⁽¹⁾: e11*94/20*7303*00

Reason(s) for Extension: Not applicable

SECTION I

- 0.1 Make (trade name of manufacturer): Brink or Thule
- 0.2 Type and general commercial description(s): 5001 / non-standard coupling ball 50
- 0.3 Means of identification of type if marked on the component⁽²⁾: Make (trade name), type and class
- 0.3.1 Location of that marking: Type plate on socket
- 0.5 Name and address of manufacturer:
- Thule Towing Systems B.V.
Industrieweg 5
7951 CX, Staphorst
Netherlands
- 0.7 In the case of components and separate technical units, location and method of affixing of the EEC approval mark: Type plate on socket plate, riveted



Dispositivo di traino tipo: 5001
Per autoveicoli: Peugeot 5008
Tipo funzionale: OE****/**

Classe e tipo di attacco: A50-X
Omologazione: e11 00-7303
Valore D: 9,7 kN

Carico Verticale max. S: 70 kg

Larghezza rimorchiabile per Caravan e T.A.T.S.: 2,55m vedere CARTA di CIRCOLAZIONE VEICOLO (motrice) + 70 cm = ..arrotondare ai 5 cm superiore (vedi D.M.28/05/125)

Massa rimorchiabile: vedi carta di circolazione dell' autoveicolo

Per verificare l' idoneità del dispositivo di traino omologato a norma CEE 94/20, all' installazione sulla vettura su cui si intende procedere al montaggio, compilare la seguente formula (se necessario declassare la massa rimorchiabile):

$$D = \frac{T \times C}{T + C} \times 0,00981 \leq 9,7 \text{ kN}$$

dove: T= Massa Complessiva Max. della motrice (in kg)
C= Massa Rimorchiabile Max. della motrice (in kg)

DA COMPILARE PER IL COLLAUDO

DICHIARAZIONE DI CORRETTO MONTAGGIO: la sottoscritta Ditta dichiara di aver montato in maniera corretta ed in conformità alle prescrizioni sia del costruttore del veicolo che del costruttore del dispositivo stesso il seguente dispositivo di attacco meccanico:

tipo:.....
Il dispositivo di attacco sopra indicato è stato installato su autoveicolo
modello:.....
targa:.....
Data:.....

TIMBRO e FIRMA

Si dichiara inoltre di aver informato l'utente del veicolo sull'USO e MANUTENZIONE del dispositivo stesso.